



Product Service

CERTIFICATE

No. Z1 091172 0028 Rev. 01

Holder of Certificate: **CAGSAN MERDIVEN VE ERISIM
EKIPMANLARI
SANAYI TICARET LIMITED SIRKETI**
Dilovasi O.S.B. 3 Kisim Meriç Cad. 1
41455 MUALLIM KÖYÜ - GEBZE, KOCAELI
TÜRKIYE

Certification Mark:



Product: **Standing step ladders
(for professional use)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier.

All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: MEC-200220009738A-000TR

Valid until: 2030-07-21

Date, 2025-07-23

(Luca Pitti)

CERTIFICATE

No. Z1 091172 0028 Rev. 01

Model(s): ANT102, ANT103, ANT104, ANT105, ANT106, ANT107, ANT108;
EVR-PRO4, EVR-PRO5, EVR-PRO6, EVR-PRO7, EVR-PRO8, EVR-PRO9, EVR-PRO10;
REG2, REG3, REG4, REG5, REG6, REG7, REG8, REG9, REG10;
VE2, VE3, VE4, VE5, VE6, VE7;
VEN102, VEN103, VEN104, VEN105, VEN106, VEN107, VEN108;

Parameters:

Model	No. of steps	Approx. dead load [kg]	Approx. max. platform height [mm]
ANT102	3	10,4	725
ANT103	4	11,6	975
ANT104	5	12,8	1225
ANT105	6	14,0	1475
ANT106	7	15,2	1725
ANT107	8	16,4	1975
ANT108	9	17,6	2225

Approx. max. dimensions [mm]:

Platform: 400x416x12

Stile: 60x20x1,25

Step: 120x31x1,2

Material:

Platform: Plywood

Stile, step: EN AW-6060

CERTIFICATE

No. Z1 091172 0028 Rev. 01

Model	No. of steps	Approx. dead load [kg]	Approx. max. height [mm]
EVR-PRO4	4	6,5	1000
EVR-PRO5	5	7,0	1250
EVR-PRO6	6	8,5	1500
EVR-PRO7	7	10,5	1750
EVR-PRO8	8	12,0	2000
EVR-PRO9	9	13,5	2250
EVR-PRO10	10	15,5	2500

Approx. max. dimensions [mm]:

Stile profile: 79 x 27 x 1,7

Step profile: 80 x 28 x 1,7

Material:

Stile, step: EN AW-6060

Model	No. of steps	Approx. dead load [kg]	Approx. max. platform height [mm]
REG2	3	9,0	750
REG3	4	10,5	1000
REG4	5	12,0	1250
REG5	6	13,5	1500
REG6	7	15,0	1750
REG7	8	16,5	2000
REG8	9	18,0	2250
REG9	10	19,5	2500
REG10	11	21,0	2750

Approx. max. dimensions [mm]:

Stile: 104,5 x 28,8 x 2,20

Step: 103,8 x 30 x 2,0

Material: EN AW-6060-T5

CERTIFICATE

No. Z1 091172 0028 Rev. 01

Model	No.of steps	Approx.dead load [kg]	Approx.max. platform height [mm]
VE2	3	14,6	750
VE3	4	17,2	1000
VE4	5	19,4	1250
VE5	6	21,5	1500
VE6	7	23,6	1750
VE7	8	24,8	2000

Approx.max.dimensions [mm]:

Stile: 104,5 x 28,8 x 2,20

Step: 103,8 x 30 x 2,0

Material: EN AW-6060-T5

Model	No. of steps	Approx.dead load [kg]	Approx.max. platform height [mm]
VEN102	3	7,6	725
VEN103	4	8,5	975
VEN104	5	9,4	1225
VEN105	6	10,3	1475
VEN106	7	11,2	1725
VEN107	8	12,1	1975
VEN108	9	13,0	2225

Approx.max.dimensions [mm]:

Platform: 250x280x2,2

Stile: 60x20x1,25

Step: 120x31x1,2

Material:

Platform: Thermoset plastics

Stile, step: EN AW-6060



CERTIFICATE

No. Z1 091172 0028 Rev. 01

Tested according to: EN 131-1:2015/A1:2019
EN 131-2:2010/A2:2017
EN 131-3:2018
EK5/AK1 17-02.4:2021